



BARCODE MARKET

93.180.86.49

[www.barcode-market.com](http://www.barcode-market.com)

# BMK ST301 Tablet Multifuncional IP67



## CARACTERISTICAS PRINCIPALES:

1. ANDROID 4.4
2. MSM8225Q (Quad-core ), a 1,2 Gh
3. Sim UMTS/GSM/GPRS/EDGE
4. 8.0M CMOS Rear Camera + 2M Front Camera
5. Memoria: RAM 1G + ROM 8G
6. Batería expandida de 7000mAh
7. Opción Lector Código de barras 1D
8. Opción NFC



BARCODE MARKET, C/ Mont 58, 08340 Vilassar de Mar, Barcelona  
93.180.86.49 \* [www.barcode-market.com](http://www.barcode-market.com)  
NIF: 46578833S

# BMK ST301

## Tablet Multifuncional IP67

General Specifications	
Operating System	Android 4.1 OS
Hardware Platform	MSM8225Q, 4 core, 1.2G
CPU	1.2GHz, 4core
RAM	RAM: 1G FLASH: 8G
Extended Storage	Micro SD, Maximum 32G
Ports	USB port: 5 pin MicroUSB; support OTG
Protection Grade	
Industrial Protection Grade	IP67
Drop Grade	Drop resistance from 1.2m
Wireless Communication	
Bluetooth	V2.1, EDR+A2DP
GPS	Provide independent GPS module interface (support Beidou Position); support RTCM2.3, RTCM3.0, CMR differential data and mobile phone GPS two sets of circuit, but can only choose one type at same time; The application program can control the open / close GPS/DBS.
WIFI	Support IEEE 802.11b/g/n
3G	WCDMA/GSM
Data Acquisition (Optional)	
Barcode Scanning	support 1D infrared SE655, 1D laser, 2D barcode
RFID	HF 13.56MHZ: support ISO/IEC 15693, ISO/IEC 14443A protocol; supports card SR176; SR1X4K (TYPE-B); I-Code2; TI RFID Tag-it HF-I, EM4135, EM4034 etc.; application software can control the open/close RFID (NFC)
Fingerprint Identification System	support the fingerprint recognition interface; support fingerprint unlock.
Physical Parameters	
Display Screen	7 inch 1280x800 IPS touchable LCD screen
Keyboard	Home, Menu, Return, ON/OFF, Volume, Reset, Barcode
Camera	2 mp front camera, 8 mp rear camera with AF/LF
Headset	General earphone interface
Vibration	With vibration prompt function
Acelerator	support
Flashlight Function	Can be used for emergency lighting
Rechargeable Battery	Li-Ion 3.7V, 7000mAh
Standby	More than 700 hours of continuous standby.
Dimension	160mm*190mm*20mm
Weight	750g
Environmental Characteristics	
Working Temperature	-20°C ~ +50°C
Storage Temperature	-40°C ~ +60°C
Humidity	5%-95% relative humidity; no condensation

